Renice X3 mSATA

50mm miniSATA (mini PCI-E form factor) SSD

Features

- ♦ SANDFORCE Controller SF-1222
- ◆ Form Factor: 50mm miniSATA (mini PCI-E form factor)
- ♦ Capacities: 25GB, 60GB, 120GB
- ♦ Size: 50.35 x 30x 3.46mm
- ♦ Net Weight: <6g</p>
- ♦ NCQ up to 32 commands
- ♦ RAID Support
- ◆ TRIM Support

Performance

Max Read Rate: 260MB/sec

♦ Max Write Rate: 200MB/sec

♦ 4kb Random Read IOPS: 30,000

♦ Access Time: 0.1ms

Power Consumption and Environment

♦ Input Voltage: 3.3V±5%

◆ Idle: <0.5W◆ Active: <0.9W

◆ Operating Temperature: 0 to 70°C
◆ Storage Temperature: -40 to 85°C

Reliability

- ♦ MTBF: >2,000,000 hours
- High and Reliable ECC capability up to 24bits/sector
- S.M.A.R.T features optimized for SSD
- Bit error monitoring and managing
- Dynamic and static wear-leveling
- Dynamic bad block management
- SMART commands and additional SSD monitoring
- ♦ 2 Years warranty

Typical Applications

- ♦ Asus EP121, EEE PC, X101
- Lenovo E220s, E420s, Y460, Y560, K26, K47A, K47G, T420s, T420, T520, L420, L520, W520, X220
- ◆ Dell M4500, M6400, M6500
- ♦ Fusion Garage JOOJOO