Renice X3 mini PCI-E

70mm mini PCI-E SATA SSD

Features

- ♦ SANDFORCE Controller SF-1222
- ♦ Form Factor: 70mm mini PCI-E
- ◆ Capacities: 25GB, 60GB, 120GB, 240GB
- ♦ Size: 69.73 x 31.5 x 3.26mm
- ♦ Net Weight: <20g</p>
- ♦ NCQ up to 32 commands
- ♦ RAID Support
- ◆ TRIM Support

Performance

- Max Read Rate: 260MB/sec
- ♦ Max Write Rate: 200MB/sec
- ♦ 4kb Random Read IOPS: 30,000
- ♦ Access Time: 0.1ms

Power Consumption and Environment

- ♦ Input Voltage: 3.3V±5%
- ◆ Idle: <0.6W◆ Active: <0.9W
- ◆ Operating Temperature: 0 to 70°C
- ♦ Storage Temperature: -40 to 85°C

Reliability

- ♦ MTBF: >2,000,000 hours
- High and Reliable ECC capability up to 24bits/sector
- ♦ S.M.A.R.T features optimized for SSD
- Bit error monitoring and managing
- Dynamic and static wear-leveling
- Dynamic bad block management
- SMART commands and additional SSD monitoring
- ♦ 2 Years warranty

Typical Applications

♦ Asus Asus Eee PC 900, Eee PC 901, Eee PC 901 Go, Eee PC S101